SUMMARY OF RATES OF INFILTRATION

SITE:	Bryneithin, Dinas Powys			
JOB No:	PC060			

SOAKAWAY		Base of	WATER LEVEL DURING TEST (m)		INFILTRATION RATE (A)	INFILTRATION RATE (B)
Pit	Cycle	Pit (m)	Start	Finish	(m/sec) - BRE Digest 365	(m/sec) - full Area
1	1	3.00	1.300	2.510	2.29E-05	1.43E-05
3	1	1.50	0.460	1.310	2.28E-05	1.76E-05
4	1	1.60	0.600	1.410	8.65E-05	6.62E-05
4	2	1.60	0.560	1.540	4.14E-05	3.82E-05
4	3	1.60	0.440	1.280	5.63E-05	3.74E-05
5	1	1.40	0.250	0.890	2.47E-05	1.26E-05
2	1	1.30	0.520	0.880	1.37E-05	6.54E-06

Note:

Infiltration Rate (A) is the standard calculation outlined in BRE Digest 365, which takes account of actual drained area of pit.

Infiltration Rate (B) is based on the principles outlined in BRE Digest 365, but also includes the full undrained area of pit.

Where only partial drainage has occurred, the quoted infiltration rate should be used as a guide only and strictly only apply to the drained portion of the pit; substantially lower rates would apply to the lower undrained section of the pit.

Infl-rates 16/02/2004