



Legend


- Site boundary.
- - - Secure site boundary fencing, minimum 1.8m high. Weld mesh anti-climb fence, to SbD standards e.g. Dulok double wire mesh fencing at 1830mm height, powder coated in black colour. With matching gates.
- - - Secondary secure fencing to playground zones. Weld mesh anti-climb fence, e.g. Dulok double wire mesh fencing at 1430mm height, powder coated in black colour. With matching gates.
- Fencing to refuse store. Timber hit and miss fencing, with concrete support posts. Minimum 2400mm high. With matching gates. Roof not included.
- Existing brick wall and metal fencing to be retained. Reclad in timber, subject to fire requirements. New lockable maintenance gate to be installed.
- Fencing to MUGA. Weld mesh anti-climb fence, to SbD standards e.g. Dulok double wire mesh fencing at 3000mm height, powder coated in black colour. With matching gates.
- Existing fence to habitat area to be retained.
- Bollards.
Refer to drawing SNPS-STL-XX-DR-L-9002 Hard Landscape Plan for details.

- G1** Lockable pedestrian gate. Single leaf gate, min. 1.2m clear opening.
- G2** Lockable vehicular gate. Double leaf gate, min. 6.0m clear opening.
- G3** Lockable vehicular gate. Double leaf gate, min. 6.0m clear opening.
- G4** Lockable pedestrian gate. Single leaf gate, min. 1.2m clear opening.
- G5** Lockable maintenance gate to Bin Store enclosure. Double leaf gate, min. 2.0m clear opening.
- G6** Lockable maintenance gate to Substation. Double leaf gate, to match existing gap.
- G7** Lockable maintenance gate. Double leaf gate, min. 2.4m clear opening.
- G8** Lockable pedestrian/ maintenance gate to Habitat area. Double leaf gate, min. 2.4m clear opening.
- G9** Lockable pedestrian/ maintenance gate. Double leaf gate, min. 2.4m clear opening.
- G10** Lockable pedestrian/ maintenance gate. Double leaf gate, min. 2.4m clear opening.
- G11** Lockable pedestrian/ maintenance gate. Double leaf gate, min. 2.4m clear opening.
- G12** Lockable pedestrian gate. Single leaf gate, min. 1.2m clear opening.
- G13** Lockable pedestrian gate. Single leaf gate, min. 1.2m clear opening.
- G14** Lockable pedestrian/ maintenance gate. Double leaf gate, min. 2.4m clear opening.
- G15** Lockable pedestrian/ maintenance gate. Double leaf gate, min. 2.4m clear opening.

STATUS	REV	DATE	DESCRIPTION
PL	PL09	02/12/21	Planning Pre-Application Consultation Issue
S3	P34	25/11/21	Updated Planning PLC
PL	PL07	30/09/20	Updated anotation and planting for planning
PL	PL06	17/09/20	Highways input update for discharge of conditions
PL	PL05	11/09/20	For discharge of conditions
PL	PL04	09/09/20	Amended for Planning Issue
PL	PL01	07/06/20	For Stage 3 Issue
S4	PL03	25/06/20	For Planning
PL	PL02	15/06/20	PAC Submission
PL	PL01	12/06/20	PAC Submission

CLIENT	REVISED BY
Vale of Glamorgan Council	AP
CHECKED BY	CS
ORIGINATOR NO	152853

CONSULTANT
STRIDE TREGLOWN
www.stridetreglow.com © Stride Treglow Limited 2020
 PROJECT
St Nicholas Primary School



Fencing and Site Security Plan
 1 : 500

DRAWING TITLE	SCALE
Fencing and Site Security Plan	1 : 500@A1
DRAWING USAGE:	
PL : Authorized and accepted	
DRAWING USAGE:	
PROJECT - ORIGINATOR - VOLUME - LEVEL - TYPE - ROLE - CLASS - NUMBER	STATUS_REVISION
SNPS-STL-XX-DR-L-9004	PL_PL09